

CALL MANAGEMENT SYSTEM

BACKGROUND OF THE INVENTION

Field of the Invention

5 The invention relates to a system for managing calls and, more particularly, to a system for managing calls for a telephone of a user using a computer of the user connected via a network to a service provider.

Background of the Invention

10 Conventionally, a single-line telephone, such as an ordinary residential telephone, does not have multiple-line telephone features, such as the ability to receive more than one call at a time, to hold a current call, or to transfer a current call. To obtain multiple-line telephone features, a user conventionally has two choices. First, the user purchases a multiple-line telephone, which may include purchasing associated telephone switching hardware and software. 15 This option, however, is potentially very costly to the user. Second, the user purchases multiple-line telephone features from a local service provider. For example, Verizon of New York, New York offers a service known as CENTREX, which provides several multiple-line features. With the CENTREX service, if a user wishes to access a multiple-line telephone feature from a single-line telephone, the user must press one of the asterisks-codes via the keypad of the telephone or 20 perform a flash via the hook state. With this option, however, a user must memorize an asterisks-code for each subscribed-to multiple-line telephone feature. Further, the accessing of the asterisks-codes may be awkward for a user during a telephone call if the keypad for the telephone is located in the handset of the telephone because the user must remove the handset from the ear and mouth of the user to access the asterisks-codes via the keypad in the handset.

SUMMARY OF THE INVENTION

It is an object of the invention to provide multiple-line telephone features for a single-line telephone of a user.

5 It is an object of the invention to provide control of a telephone of a user via a computer of the user.

The invention includes a system, an apparatus, a method, and an article of manufacture.

10 The system of the invention includes a computer system to provide at least one telephone feature to a telephone of a user, the computer system receiving instructions regarding said at least one telephone feature via a network from a graphical user interface operating on a computer of the user. The computer system comprises: an application server to interact with the telephone of the user and to provide said at least one telephone feature for the telephone; and a network server layer to interact with the application server, to interact via the network with the computer of the user, and to provide via the network the graphical user interface to the computer, the graphical user interface to operate said at least one telephone feature for the telephone of the user via the network, the network server layer, and the application server.

15 The method of the invention includes a method comprising the steps of: providing a graphical user interface via a network to a computer of a user; controlling a telephone of the user according to input received from the graphical user interface on the computer of the user; and
20 updating the graphical user interface on the computer of the user via the network. The method further comprises the steps of: receiving a call information regarding the telephone; sending a refresh request to the graphical user interface to request an update on a state of the telephone;

and receiving an update request from the graphical user interface for the update on the state of the telephone.

The system of the invention includes a system comprising: means for providing a graphical user interface via a network to a computer of a user; means for controlling a telephone of the user according to input received from the graphical user interface on the computer of the user; and means for updating the graphical user interface on the computer of the user via the network. The system further comprises: means for receiving a call information regarding the telephone; means for sending a refresh request to the graphical user interface to request an update on a state of the telephone; and means for receiving an update request from the graphical user interface for the update on the state of the telephone.

The apparatus of the invention includes a computer system for performing the method of the invention.

The apparatus of the invention includes a computer-readable medium comprising software for performing the method of the invention.

A "computer" refers to any apparatus that is capable of accepting a structured input, processing the structured input according to prescribed rules, and producing results of the processing as output. Examples of a computer include: a computer; a general purpose computer; a supercomputer; a mainframe; a super mini-computer; a mini-computer; a workstation; a micro-computer; a personal computer; a laptop computer; a server; an interactive television; and a hybrid combination of a computer and an interactive television. A computer can have a single processor or multiple processors, which can operate in parallel and/or not in parallel. A computer also refers to two or more computers connected together via a network for transmitting

or receiving information between the computers. An example of such a computer includes a distributed computer system for processing information via computers linked by a network.

A "computer-readable medium" refers to any storage device used for storing data accessible by a computer. Examples of a computer-readable medium include: a magnetic hard disk; a floppy disk; an optical disk, such as a CD-ROM and a DVD; a magnetic tape; a memory chip; and a carrier wave used to carry computer-readable electronic data, such as those used in transmitting and receiving e-mail or in accessing a network.

"Software" refers to prescribed rules to operate a computer. Examples of software include: software; code segments; instructions; computer programs; and programmed logic.

A "computer system" refers to a system having a computer, where the computer comprises a computer-readable medium embodying software to operate the computer.

A "network" refers to a number of computers and associated devices that are connected by communication facilities. A network involves permanent connections such as cables or temporary connections such as those made through telephone or other communication links. Examples of a network include: an internet, such as the Internet; an intranet; a local area network (LAN); a wide area network (WAN); and a combination of networks, such as an internet and an intranet.

A "telephone network" refers to a network to route a telephone call. Example of a telephone network include: public switch telephone network (PSTN); and the Internet. A telephone network is accessed, for example, via an access gateway, a network gateway, or a soft switch.

Moreover, the above objects and advantages of the invention are illustrative, and not exhaustive, of those which can be achieved by the invention. Thus, these and other objects and

advantages of the invention will be apparent from the description herein, both as embodied herein and as modified in view of any variations which will be apparent to those skilled in the art.

BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments of the invention are explained in greater detail by way of the drawings, where the same reference numerals refer to the same features.

Figure 1 illustrates a plan view of the invention.

Figure 2 illustrates a state diagram depicting exemplary relationships between exemplary call states of a telephone of a user.

Figure 3 illustrates a flow diagram for connecting a telephone of a user to a service provider.

Figure 4 illustrates a flow diagram for dialing a telephone number using a telephone of a user.

Figure 5 illustrates a flow diagram for initiating a telephone feature from a computer of a user.

Figure 6 illustrates a flow diagram for receiving a call for a telephone of a user.

Figure 7 illustrates an exemplary graphical user interface (GUI).

Figure 8 illustrates the GUI of Figure 7 with additional features.

Figure 9 illustrates the GUI of Figure 8 with additional features.

Figure 10 illustrates a plain view of another embodiment of the invention.

Figure 11 illustrates a plain view of yet another embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

The invention integrates and improves upon call processing technologies and network technologies for new, unique, and useful telephone-related services for a user. Specifically, the invention controls a telephone of the user via a computer of the user. The computer of the user is connected via a network to a service provider to control the telephone of the user. The user initiates telephone calls via either the telephone of the user or the computer of the user and accesses telephone features provided by the service provider via the computer of the user. The service provider receives incoming calls for the telephone of the user and administers outgoing calls for the user. The service provider also synchronizes a call state of the telephone of the user with a representation of the call state on the computer of the user.

With the invention, the user is able to receive calls from many different types of telephony devices and access telephone features for addressing the received calls. Further, no software to control the telephone of the user preferably needs to be installed on the computer of the user beyond a network browser. In a preferred embodiment, the user invokes the telephone features to control the telephone of the user using a network browser on the computer of the user.

With the invention, the user is able to turn any telephone into a telephone having office-like features, including numerous multi-line features. As long as the user has access to a telephone and a connection from the computer to the service provider, the user is able to turn the telephone of the user into an office-like telephone. Further, the invention is available anywhere in the world where the user has access to a telephone, where the computer has access to a network for contacting the service provider, and where the service provider has access to control the telephone.

Figure 1 illustrates a plan view of the invention. The invention includes a user side 1 and a service provider side 2. The user side 1 includes a telephone 3 of a user and a computer 6 of the user. The service provider side 2 includes an application server 4 and a network server layer 5.

The telephone 3 of the user is implemented with a wide variety of telephones. Examples of the telephone 3 include: a single-line telephone; a multiple-line telephone; a direct dial-in telephone; a public pay telephone; a mobile telephone; a wireless telephone; and a soft client (e.g., a web telephone).

The telephone 3 of the user does not need to be known to the service provider side 2 prior to the computer 6 connecting the service provider side 2. With the invention, the telephone 3 is not required to be registered with the service provider side 2, as with a local telephone company or a long distance telephone company. Instead, the user is registered with the service provider side 2 and, upon connecting the computer 6 to the service provider side 2, is able to identify any telephone 3 for use with the invention. As an example, if the user is in an airport, the computer 6, which is a laptop computer, for instance, is connected to the network server layer 5 via a mobile telephone of the user, and the telephone 3 is a public pay telephone located next to the user in the airport. As another example, if the user is visiting a friend who has a single-line telephone, the computer 6, which is a laptop computer, for instance, is connected to the network server layer 5 via a mobile telephone of the user, and the telephone 3 is the single-line telephone of the friend.

A telephone network 10 connects the telephone 3 and the application server 4. The telephone network bridges the user side 1 and the service provider side 2. The application server 4 is connected to the telephone network 10 via, for example, an access gateway, a network

gateway, or a soft switch. Preferably, the telephone 3 communicates with the application server 4 via the telephone network 10 using an Internet protocol (IP) telephony protocol via an access gateway.

The application server 4 connects the telephone 3 to the network server layer 5. In addition, the application server 4 manages the services for the service provider side 2, including maintaining and administering telephone features 11, sending calls on behalf of the user via the computer 6 or the telephone 3, and receiving calls for the telephone 3. Preferably, the application server 4 is implemented with the invention disclosed in co-pending U.S. Patent Application No. 09/418,130, filed October 12, 1999, which is incorporated herein by reference.

The telephone features 11 include any service usable with the telephone 3. Examples of the telephone features 11 include the following: a multiple-line telephone feature; a dial number feature; a transfer feature; an answer/talk feature; a hold feature; a conferencing feature; a release feature; a voicemail feature; a do not disturb feature; and a call forwarding feature. Exemplary telephone features are further discussed with respect to the exemplary GUIs of Figures 7-9.

The application server 4 controls the telephone 3. The application server 4 maintains zero or more calls for the user depending on the hardware of the service provider side 2 and depending on the number of call lines to which the user subscribes.

The application server 4 maintains one or more call states for the telephone 3. Examples of a call state for the telephone 3 include the following: an idle call state; a non-idle call state; a call from state; a call to state; a talking state; and a held state. Figure 2 illustrates a state diagram depicting exemplary relationships between exemplary call states for the telephone 3 as managed by the application server 4.

With the invention, the application server 4 is able to receive calls from a variety of communication devices, such as for example: a standard residential telephone; a standard business telephone; a wireless mobile telephone; a soft client (e.g., a web telephone); a pager; and a public pay telephone.

5 The network 12 connects the application server 4 and the network server layer 5. Preferably, the network 12 is an intranet. As an option, the network 12 is the Internet. Preferably, the network 12 uses a three-layer system to couple the application server 4 and the network server layer 5. The three-layer system comprises a client call protocol layer (CCP), which is on top of a remote invocation (RMI) layer, which is on top of a transmission control
10 protocol/Internet protocol (TCP/IP) layer. The CCP layer includes a bi-directional protocol between the application server 4 and the network server layer 5. The RMI layer transports object-oriented technology between the application server 4 and the network server layer 5. The RMI layer is preferably implemented using the Java software and is able to start remote Java software. Information on Java software is available at www.java.sun.com. The TCP/IP layer
15 comprises a TCP/IP socket. Alternatively, instead of the preferred three-layer system, the network 12 uses a bi-directional TCP/IP socket-based protocol.

The network server layer 5 connects the application server 4 and the computer 6. The network server layer 5 mediates communications between the application server 4 and the computer 6. Preferably, the network server layer 5 is a web server, such as an Apache web server
20 available from The Apache Software Foundation of Forest Hill, Maryland. Further information on the Apache web server is available at www.apache.org.

The network server layer 5 maintains a GUI 13. Preferably, the GUI 13 is in the hypertext markup language (HTML) and is usable with a network browser 19 of the computer 6.

Exemplary GUIs are illustrated in and discussed with respect to Figures 7-9. The network server layer 5 provides the GUI 13 to the computer 6 as GUI 17. The network server layer 5 updates the GUI 17 regarding a representation of a call state of the telephone 3 and synchronizes a call state of the telephone 3 with a representation of the call state for the GUI 17. The network server layer 5 provides information to and from the application server 4 regarding the GUI 17.

The network server layer 5 maintains network communication software (NCS) 14. Preferably, the NCS 14 is a Java applet. The NCS 14 is provided along with the GUI 13 to the computer 6 as NCS 18. The NCS 18 receives prompts from the network server layer 5 for receiving real-time updates of the call state of the telephone 3 and the service provider side 2.

The network server layer 5 maintains a servlet engine 15. Preferably, the servlet engine 15 is a Java server engine, such as the Apache Jserv by the Apache Software Foundation of Forest Hill, Maryland. Information on Apache Jserv is available at java.apache.org.

In general, the network server layer 5 updates the GUI 17 for a call on telephone 3 transitioning from one state to another state. As an example, the network server layer 5 updates the GUI 17 to represent an idle call state when no calls are present on the telephone 3 and a non-idle call state when at least one call is present on the telephone 3. Examples of states of the telephone, as administered by the application server 4, are illustrated in Figure 2.

The network server layer 5 provides to the GUI 17 an indication as to which telephone features 11 are accessible via the GUI 17 and an update of accessibility for the accessible telephone features 11. For example, if a conferencing feature is one of the telephone features 11, the user is able to have conference calls from the telephone 3. If the user does not subscribe to the conferencing feature, the network server layer 5 does not provide an indication that the conferencing feature is available to the user via the GUI 17. If, however, the user subscribes to

the conferencing feature, the network server layer 5 provides an indication of accessibility to the conferencing feature and updates this indication of accessibility as the conferencing feature is in use and not in use. As another example, if the user subscribes to a hold feature of the telephone features 11, the user is able to hold a call. If a call is present, the network server layer 5 updates the GUI 17 that the hold feature is available for selection by the user. If, however, no call is present and the telephone 3 is in an idle state, the network server layer 5 updates the GUI 17 that the hold feature is unusable by to the user.

The network 16 connects the network server layer 5 and the computer 6. The network 16 bridges the user side 1 and the service provider side 2. Preferably, the network 16 is an intranet. As an option, the network 16 is the Internet. Preferably, the network 16 is implemented with two two-layer systems: (1) an hypertext transfer protocol (HTTP) layer, which is on top of a first TCP/IP layer; and (1) a client push protocol (CPP) layer, which is on top of a second TCP/IP layer. The HTTP layer is bi-directional, and the CPP layer is uni-directional from the network server layer 5 to the computer 6. The HTTP layer permits the computer 6 to pull information from the network server layer 5. The CPP layer provides an additional layer of communication between the computer 6 and the network server layer 5 that is unavailable with the HTTP layer. Each of the two TCP/IP layers comprise a TCP/IP socket for transferring information between the network server layer 5 and the computer 6 such that the network 16 preferably includes two TCP/IP sockets.

The GUI 17 and the NCS 18 preferably use different techniques to communicate with the network server layer 5. The GUI 17 preferably uses the HTTP layer, and the NCS 18 preferably uses the CPP layer. The CCP layer pushes information from the network server layer 5 to the computer 6. Preferably, the CCP layer pushes information from the servlet engine 15 of the

network server layer 5 to the NCS 18 of the computer 6. With the CCP layer, real-time updates as to the call state of the telephone 3 and the status of the service provider side 2 are provided to the computer 6.

The computer 6 resides on the user side 1 and provides the user with the ability to control the telephone 3 via the service provider side 2. The computer 6 includes the GUI 17, the NCS 18, and a network browser 19. The network browser 19 is any type that is able to support the GUI 17. Examples of the network browser 19 include the Internet Explorer by Microsoft Corporation of Redmond, Washington and the Netscape Navigator by America Online of Dulles, Virginia. The network browser 19 is used to connect the computer 6 to the network server layer 5 to initiate control of the telephone 3 via the server provider side 2.

With the invention, no information is stored on the computer 6 regarding calls of the user and telephone features 11 subscribed to by the user. Instead, all such information is stored by the network server layer 5 on the service providers side 2.

To update the GUI 17, the network server layer 5 prompts the computer 6 to request from the network server layer 5 an update of the call state of the telephone 3. Preferably, the network server layer 5 prompts the computer 6 using the CPP layer of the network 16. Preferably, when the GUI 17 needs to be updated, the network server layer 5 via the servlet engine 15 prompts the NCS 18 via the CPP layer of the network 16 to request an update of the GUI 17. The NCS 18 in turn prompts the GUI 17 to request an update from the network server layer 5, and the GUI 17 requests an update from the network server layer 5 via the HTTP layer of the network 16. The GUI update feature of the invention is further discussed with respect to Figures 4-6.

With the invention, no software is installed on the computer 6 at run time. Instead, all that is required is a network browser 19 on the computer 6. The GUI 17 and the NCS 18 are

provided from the network server layer 5 and are copies of the GUI 13 and the NCS 14, respectively. In addition, no plug-ins or extra security permissions are preferably needed on the computer 6 to run the GUI 17 and the NCS 18.

The invention permits extendable architecture for the service provider side 2. As illustrated in Figure 1, the application server 4 and the network server layer 5 are implemented separately. In one embodiment, the service provider side 2 comprises a computer system comprising one computer system for implementing the application server 4 and another computer system implementing the network server layer 5. The application server 4 and the network server layer 5 do not need to reside in the same complex and, as an option, are located at geographically distinct locations. In another embodiment, the application server 4 and the network server layer 5 are implemented in a single computer system at the same geographic location.

Figures 3-6 illustrate the information flow of the invention and refer to the plan view of the invention illustrated in Figure 1.

Figure 3 illustrates a flow diagram for connecting the telephone 3 to the service provider side 2. In block 31, the computer 6 contacts the network server layer 5 via the network 16. Preferably, the network browser 19 of the computer 6 contacts the network server layer 5 via the network 16. Preferably, the network server layer 5 operates a web site accessible via the network browser 19 on the computer 6. Once the web site is accessed by the computer 6, all software that is required to control the telephone 3 via the computer 6 is preferably downloaded from the web site operated by the network server layer 5, which is discussed below for block 32. As an example, using the network browser 19 and the Internet, the user visits the web site maintained by the service provider side 2.

In block 32, the network server layer 5 provides the GUI 13 and the NCS 14 via the network 16 to the computer 6. The provided GUI 13 is represented as the GUI 17 on the computer 6, and the NCS 14 is represented as the NCS 18 on the computer 6. Preferably, the web site operated by the network server layer 5 downloads the GUI 17 and the NCS 18 to the computer 6 via the HTTP layer of the network 16. Preferably, no software other than the GUI 17 and the NCS 18 needs to be downloaded to control the telephone 3 via the computer 6. Further, no additional software is required to be installed on the computer 6 other than the network browser 19. All information regarding the services subscribed to by the user are stored in the network server layer 5 and are represented by the GUI 17.

In block 33, the GUI 17 of the computer 6 registers the telephone 3 of the user with the network server layer 5. Once the GUI 17 and the NCS 18 are downloaded from the network server layer 5, the GUI 17 and the NCS 18 start up via the network browser 19. As an example, at the web site maintained by the service provider side 2, the user elects to control a telephone of the user, and a separate window, for instance, on the computer 6 is opened using the network browser 19 to run the GUI 17 and the NCS 18. As part of the initiation process, the GUI 17 prompts the user to enter the telephone number of the telephone 3. Preferably, the GUI 17 includes a list of previously registered telephone numbers which are available to the user for selection. The list of previously registered telephone numbers is maintained by the network server layer 5 and is included with the GUI 17. The user selects one of the previously registered telephone numbers or enters a new telephone number. Once entered, the GUI 17 forwards the telephone number to the network server layer 5 via the network 16. The communication between the computer 6 and the network server layer 5 for block 33 is preferably via the HTTP layer of

the network 16. Once the network server layer 5 receives the telephone number of the telephone 3, the network server layer 5 forwards the telephone number to the application server 4.

In block 34, the application server 4 controls the telephone 3 via the telephone features 11. The application server 4 controls all calls to and from the telephone 3 and all calls from the computer 6 for the telephone 3. Once the application server 4 receives the telephone number for the telephone 3 from the network server layer 5 via the network 12, the application server 4 assumes control of the telephone network connections to the telephone 3 via, for example, an access gateway, a network gateway, or a soft switch.

In block 35, the network server layer 5 stores information on both the user and calls and also synchronizes the GUI 17 of the computer 6 with the telephone 3. The network server layer 5 stores, for example: information on calls to and from the telephone 3 and from the computer 6; information regarding the services subscribed to by the user, including the telephone features 11 subscribed to by the user; and the telephone number of the telephone 3. The network server layer 5 synchronizes the call state of the telephone 3 with a representation of the call state for the GUI 17. The synchronization is discussed further below with respect to Figures 4-6, and particularly blocks 44-48 in Figure 4.

Figure 4 illustrates a flow diagram for dialing a telephone number using the telephone 3. This scenario is differentiated from the user dialing a telephone number using the GUI 17, which is discussed with respect to Figure 5.

In block 41, the user dials a telephone number using the telephone 3.

In block 42, the telephone 3 sends call information regarding the dialed telephone number to the application server 4 via the telephone network 10.

In block 43, the application server 4 processes the call information received from the telephone 3. Using the call information, the application server 4 accesses a telephone network (not shown) and dials the dialed telephone number. From the telephone 3, the user hears the number being dialed, and the desired telephone number ringing if the connection is successful.

5 In block 44, the application server 4 sends a call message to the network server layer 5 via the network 12. The call message notifies the network server layer that the call state of the telephone 3 has changed from an idle state to a non-idle state, such as a call from state as illustrated in Figure 2.

10 In block 45, after receiving the call message from the application server 4, the network server layer 5 sends a refresh request to the NCS 18 requesting that the GUI 17 request an update from the network server layer 5. Preferably, the servlet engine 15 sends the refresh request via the CCP layer of the network 16 to the NCS 18. The refresh request sent by the network server layer 5 to the NCS 18 notifies the GUI 17 that the GUI 17 needs to be refreshed.

15 In block 46, the GUI 17 processes the refresh request received from the network server layer 5. Preferably, the NCS 18, which received the refresh request, forwards the refresh request to the GUI 17, which interacts with the network browser 19.

20 In block 47, the GUI 17 sends an update request to the network server layer 5 via the network 16. The GUI 17 in conjunction with the network browser 19 sends the update request to the network server layer 5. Preferably, the update request is sent from the GUI 17 to the network server layer 5 via the HTTP layer of the network 16.

In block 48, the network server layer 5 sends updated telephone information to the GUI 17 via the network 16. Preferably, the updated telephone information is sent to the GUI 17 via

the HTTP layer of the network 16. As the telephone call continues and the call state of the telephone 3 is changed, the GUI 17 is updated according to blocks 44-48.

Figure 5 illustrates a flow diagram for initiating a telephone feature 11 from the computer 6 of the user. In block 51, the user initiates a telephone feature 11 using the GUI 17. For example, the user initiates the dial number feature or the hold feature of the telephone features 11. Any conventional technique is employed to permit the user to interact with the GUI 17 and select a telephone feature.

In block 52, the GUI 17 sends a call management direction to the network server layer 5 via the network 16. The call management direction indicates to the network server layer 5 that the user initiated a particular telephone feature 11. Preferably, the call management direction is sent via the HTTP layer of the network 16.

In block 53, the network server layer 5 sends a telephone feature message to the application server 4 via the network 12. The telephone feature message indicates to the application server 4 that a particular telephone feature 11 needs to be administered on behalf of the user. The telephone feature message is sent via the CCP layer of the network 12.

In block 54, the application server 4 administers the selected telephone feature 11. As an example, if the selected telephone feature 11 is the dial number feature, the application server 4 dials the selected number and rings the telephone 3 via the telephone network 10. When the user answers the telephone 3, the user hears the dialing and ringing of the telephone number selected in block 51. As another example, if the selected telephone feature 11 is the hold feature, the application server 4 places on hold the call selected by the user using the GUI 17 in block 51.

In block 55, the network server layer 5 synchronizes the GUI 17 with the telephone 3. The application server 4 communicates with the network server layer 5 via the network 12 as to

the status of the call state of the telephone 3. The network server layer 5 and the GUI 17 communicate via network 16 as discussed above in blocks 44-48 to update the GUI 17 as to the status of the telephone 3. The network server layer 5 synchronizes the call state of the telephone 3 with a representation of the call state for the computer 6.

5 Figure 6 illustrates a flow diagram for receiving a call on the telephone 3 of the user. In block 61, the application server 4 receives an incoming call on behalf of the telephone 3. Because the telephone 3 is registered with the application server 4, the application server 4 monitors the incoming telephone calls for telephone 3 and receives them on behalf of telephone 3.

10 In block 62, the application server 4 rings the telephone 3 via the telephone network 10.

15 In block 63, the network server layer 5 synchronizes the GUI 17 with the telephone 3. The application server 4 communicates with the network server layer 5 via the network 12 as to the status of the call state of the telephone 3. The network server layer 5 and the GUI 17 communicate via network 16 as discussed above in blocks 44-48 to update the GUI 17 as to the status of the telephone 3. The network server layer 5 synchronizes the call state of the telephone 3 with a representation of the call state for the computer 6.

20 Various embodiments of the GUI 13, which is provided to the computer 6 as GUI 17, are discussed with respect to Figures 7-9. The various exemplary features of the exemplary GUIs illustrated in Figures 7-9 are combinable and separable as desired.

25 Figure 7 illustrates an exemplary GUI 71 usable as the GUI 13 and GUI 17. The GUI 71 interacts with the network browser 19, such as the Microsoft Internet Explorer network browser. The GUI 71 includes icons, some of which are user selectable, and display areas.

The GUI 71 includes icons identifying the service provider and the GUI. Service provider icon 72 designates a service provider administering the service provider side 2. Product icon 73 designates the name of the GUI 71 and the company providing the GUI 71.

Phone list display area 74 is a pull-down menu listing available telephone lists.

- 5 Examples of telephone lists include: a business phone group list, a personal phone list, and a recent calls phone list. After a phone list is selected from area 74, the numbers available from the selected phone list are displayed in a phone list entries display area 75, which is a pull-down menu.

10 As an example of areas 74 and 75, with the business group phone list, the user selects the business group phone list from area 74 and selects a name from area 75 corresponding to a member within the business group. The business group is, for instance, a company employing the user, and the business group phone list includes names of fellow employees in the company. The business group phone list is, for example, set by the company of the user, where the company subscribes to the service provider on behalf of the user.

15 As another example, with the personal phone list, the user selects the personal phone list from area 74 and a name from area 75. The personal phone list is configurable by the user.

20 As a further example, with a recent calls phone list, the user selects the recent calls phone list from area 74 and selects a listing from area 75 corresponding to a recently dialed number or a recently received number. The listings in area 75 are, for example, names, numbers, time/date stamps for calls, and/or a combination of these. The recent call phone list is a dynamic list, which is updated on a first-in-first-out basis.

Dial number area 76 displays a number the user desires to call. Area 76 displays a number manually entered by the user using, for example, the keyboard of the computer 6 or displays a number selected via areas 74 and 75.

Dial icon 77 dials a telephone number. When icon 77 is selected by the user, the number displayed in area 76 is dialed according to the invention. If the telephone 3 is on hook, the telephone 3 rings when the application server 4 administers the dial number feature. Selecting icon 77 initiates the dial number feature of telephone features 11.

Call area 78 displays current calls of the telephone 3. The active call in area 78 is the call currently connected to telephone 3 and is indicated in area 78 as "Talking" or "Ringing." For example, in Figure 7, the first call is active, as indicated by the "Talking" status. The maximum number of calls displayable in area 78 preferably corresponds to the maximum number of calls provided by the service provider side 2 or by the number of virtual lines subscribed to by the user. The highlighted call in area 78 is a selected call. By default, the selected call is generally the active call, unless the user selects a different call as a highlighted call.

Each line in area 78 includes a cell 78a for the name of the party on the call, a cell 78b for the number of the party on the call, and a cell 78c for the status of the call (e.g., ringing, talking, holding). For cell 78a, the name of the party is known and displayed if the user identifies the name of the party prior to dialing the number or if the name of the party is identifiable from a received call. If the name of the party on the call is unknown, cell 78a is blank. As an option, a time/date stamp is displayed in cell 78a if the name of the party is unknown. For cell 78b, if the user dialed the number or if the number of the party is identifiable from a received call, the number of the party on the call is known and displayed. If the number of the party on the call is unknown, cell 78b is blank. As an example, when the icon 77 is selected by the user, the number

in area 76 is displayed in area 78 in cell 78b along with the name of the called party, if known, in cell 78a and the status of the call in cell 78c.

Transfer icon 79 transfers the highlighted call in area 78 to the number displayed in area 76. The transferred-to number is, for example, the telephone number of a co-worker or voicemail. The highlighted call is transferred from telephone 3 to the transferred-to party, and the highlighted call is disconnected from the telephone 3. Selecting icon 79 initiates the transfer feature of telephone features 11.

Answer/talk icon 80 allows the user to answer an incoming call when there is another call in progress or to continue with a call on hold. When another call is incoming, the GUI 71 is updated by listing the new incoming call in area 78. To answer the new incoming call, the user selects the incoming call in area 78, which is then highlighted, and selects icon 80. If no other calls are active in area 78, and an incoming call is received, the user preferably answers the telephone 3 using the telephone 3. If a call is on hold, the icon 80 is used to retrieve the call on hold. To retrieve a call on hold, the user selects the call in area 78, which is then highlighted, and selects icon 80. When the icon 80 is selected, any active calls in area 78 are placed on hold. Selecting icon 80 initiates the answer/talk feature of the telephone features 11 and, if another call is placed on hold, initiates the hold feature of the telephone features 11.

Hold icon 81 allows user to place an active call on hold. The hold feature places an active call on hold until the call is retrieved by the user or the held party hangs up the telephone. To place the active call on hold, the user selects icon 81. To place the active call on hold, the user selects icon 81. Selecting icon 81 initiates the hold feature of the telephone features 11.

Conference icon 82 initiates a conference call with the parties listed in area 78. Calls are added and deleted to the conference call by highlighting a desired call and selecting the

appropriate icon. Selecting icon 82 initiates the conferencing feature of the telephone features 11.

Release icon 83 allows the user to disconnect a call. Selecting icon 83 releases the call highlighted in area 78. An active call is also released by the user hanging up the telephone 3.

5 Selecting icon 83 initiates the release feature of the telephone features 11.

Message waiting icon 84 displays the number of messages waiting in the voicemail of the user. Selecting icon 84 is equivalent to selecting icon 77 with the voicemail number of the user displayed in area 76. Selecting icon 84 initiates a voice mail feature in the telephone features 11.

Do not disturb icon 85 allows the user to make the telephone 3 appear busy. Incoming
10 calls are answered by the voicemail of the user or receive a busy signal. Selecting icon 85 initiates the do not disturb feature of the telephone features 11.

Call forwarding icon 86 forwards all incoming calls to the number displayed in call forwarding display area 87. Selecting icon 86 initiates the call forwarding feature in the telephone features 11.

Log out icon 88 logs out the user. When the user logs out, a message is sent to the network server layer 5 that the user is no longer interested in receiving updates, the window is closed, and the GUI 17 and the NCS 18 are removed from the computer 6. Selecting icon 88 initiates a log out feature in the telephone features 11.

Help icon 89 provides the user with information regarding interacting with the GUI 71.

20 Figure 8 illustrates an exemplary GUI 91, which is the combination of the GUI 71 of Figure 7 along with a content central display area 92 and a resource channels display area 102. With areas 92 and 102, the GUI 91 operates as a web portal. A web portal provides access to, for example, web sites and network services, such as e-mail, forums, search engines, and on-line

shopping malls. Aspects of the GUI 91 which are identical to those in the GUI 71 are not discussed.

Content central display area 92 displays messages from a personalized information provider. The messages include message information 93. An e-mail icon 94 is available for saving the information 93 in the e-mail of the user. A trash can icon 95 is available for deleting the message 93. Instead of icons 94 and 95, alternative techniques are available for implementing saving and deleting messages 93.

Resource channels display area 102 includes links to at least one organization, such as a service provider, a business, and a person. For each link, area 102 includes an identifier icon 103 of the organization, a network icon 104, and a telephone icon 105. By selecting icon 104, the website of the organization identified by icon 103 is contacted. Preferably, when icon 104 is selected, a new window is displayed via the network browser 19 for the selected organization. Telephone call icon 105 initiates a telephone call to the organization identified by icon 103. Using the dial number feature in telephone features 11, the telephone number of the organization is dialed. Selecting icon 105 is equivalent to the user selecting icon 77 for a number displayed in area 76 corresponding to the desired organization.

Figure 9 illustrates an exemplary GUI 111, which is a combination of the GUI 91 in Figure 9 along with a search feature and an advertisement. Aspects of the GUI 111 which are identical to those in the GUI 91 are not discussed. To use the search feature, the user selects a phone list from phone list area 74. In search display area 112, the user enters search criteria. After the user initiates the search (e.g., by hitting the "enter" key on the keyboard of the computer 6), a search of the phone list selected in area 74 is conducted for the information displayed in area 112. The results of the search are preferably displayed in a secondary window

initiated by the network browser 19. When a result in the secondary window is selected by the user, the number for the selected result is displayed in area 76, and the secondary window is closed.

Advertisement area 113 displays an advertisement. Preferably, a fee for the advertisement is paid by an advertiser to the server provider maintaining the server provider side 2. As an option, area 113 is updated on a periodic or aperiodic basis as discussed above for blocks 44-48 in Figure 4.

The invention is described as controlling a single telephone 3 from the computer 6. As an option, multiple telephones are controllable from the computer 6. This option is desirable, for example, for use by a receptionist. In one embodiment, the GUI 17 is modified to control multiple telephones. For example, if the GUI 17 is implemented with the GUI 71 of Figure 7, the GUI 17 includes an area 78 as for each telephone controlled by the GUI 17. Figure 10 illustrates a plain view of the invention where the GUI 17 controls two telephones, namely telephone 3 and telephone 121. Telephone 121 is connected to the network server layer 5 via telephone network 122, which may be the same as or different than the telephone network 10. The telephone features 11 are available to the computer 6 for controlling the telephones 3 and 121. If the GUI 17 is implemented with the GUI 71 of Figure 7, the GUI 17 includes an area 78 corresponding to telephone 3 and another area, similar to area 78, corresponding to telephone 121.

In another embodiment for controlling multiple telephones, instead of using a single GUI 17 and a single NCS 18 to control the multiple telephones from the computer 6, multiple GUIs and multiple NCSs are used by the computer 6. As an option, multiple GUIs and a single NCS for the computer 6 are used to control multiple telephones. Figure 11 illustrates a plain

view of the invention where the GUI 17 and the NCS 18 control telephone 3 and where the GUI 131 and the NCS 132 control telephone 121. The GUI 131 and the NCS 132 are downloaded from the network server layer 5 to the computer 6 and are copies of the GUI 13 and the NCS 14, respectively.

5 The embodiments and examples discussed herein are non-limiting examples.

The invention is described in detail with respect to preferred embodiments, and it will now be apparent from the foregoing to those skilled in the art that changes and modifications may be made without departing from the invention in its broader aspects, and the invention, therefore, as defined in the claims is intended to cover all such changes and modifications as fall
10 within the true spirit of the invention.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
220